



APE Single Acting Diesel Impact Hammer

THE WORLD'S LARGEST PILEDRIVERS

Model D260-42

SPECIFICATIONS

Stroke at Maximum Rated Energy	135 in (343 cm)
Maximum Rated Energy (Setting 4)	664,850 ft-lbs (874.25 kNm)
(Setting 3)	535,226 ft-lbs (725.63 kNm)
(Setting 2)	425,601 ft-lbs (577.01 kNm)
Minimum Rated Energy (Setting 1)	315,977 ft-lbs (428.38 kNm)
<i>(VARIABLE THROTTLE ALLOWS FOR INFINITE FUEL SETTING)</i>	
Maximum Obtainable Stroke	150 in (381 cm)
Maximum Obtainable Energy	716,500 ft-lbs (971.39 kNm)
Speed (Blows Per Minute)	34-53

WEIGHTS (APPROXIMATE)

Piston	57,320 lbs (26,000 kg)
Hammer Weight (Includes Trip Device)	118,830 lbs (53,900 kg)
Typical Operating (Weight With Offshore Leader)	Consult Factory

CAPACITIES

Fuel Tank (Runs on Diesel or Bio-Diesel)	95 Gal (359.5 Liters)
Oil Tank	26 Gal (98.4 Liters)

CONSUMPTION

Diesel or Bio-Diesel	21.6 Gal/hr (81.7 Liters/hr)
Oil Tank	2 Gal/hr (7.57 Liters/hr)
Grease	8 to 10 Pumps Every 20 Minutes of Operation Time.

STRIKER PLATE

Weight	2,400 lbs (1,089 kg)
Diameter	30 in (76.2 cm)
Area	706 in ² (4,555 cm ²)
Thickness	12 in (30.48 cm)

CUSHION MATERIAL

Type/Qty	Micarata / 3 each
Diameter-DB32	30 in (76.2 cm)
Thickness	1 in (2.54 cm)
Type/Qty	Aluminum / 4 each
Thickness	1/2 in (1.27 cm)
Diameter	30 in (76.2 cm)
Total Combined Thickness	5 in (12.7 cm)
Area	706 in ² (4,555 cm ²)
Elastic-Modulus	285 ksi (1,965 mpa)
Coeff. of Restitution	0.8

OFFSHORE LEADER

Offshore for 98 in / 2.5 meter piles and under	Consult Factory
--	-----------------


MINIMUM BOX LEAD SIZE / OPERATING LENGTH

Minimum Box Leader Size	Consult Factory
Hammer Operating Length with Box Helmet	Consult Factory




Image may not represent actual Model


Optional Variable Throttle Control



Cushion Material



9" Well Stack up



Specifications may vary due to site conditions, specific hammer conditions or product set up.
 Specifications may change without notice.
 Consult the factory for details on any specific product (800) 248-8498.
 Copyright © 2022 American Piledriving Equipment Inc. All Rights Reserved

