

APE Single Acting Diesel Impact Hammer

THE WORLD'S LARGEST PILEDRIVERS

Model D128-42

SPECIFICATIONS

Stroke at Maximum Rated Energy Maximum Rated Energy (Setting 4) (Setting 3) (Setting 2) Minimum Rated Energy (Setting 1) VARIABLE THROTTLE ALLOWS FOR INFINITE FUEL SETTING)

Maximum Obtainable Stroke Maximum Obtainable Energy Speed (Blows Per Minute)

WEIGHTS (APPROXIMATE)

Piston Anvil Anvil Cross Sectional Area Hammer Weight (Includes Trip Device) Typical Operating (Weight With Offshore Leader)

CAPACITIES

Fuel Tank (Runs on Diesel or Bio-Diesel) Oil Tank

<u>CONSUMPTION</u>

Diesel or Bio-Diesel Oil Tank Grease

STRIKER PLATE

Weight Diameter Area Thickness

CUSHION MATERIAL

Type/Qty Diameter-DB32 Thickness

Type/Qty Thickness Diameter Total Combined Thickness Area Elastic-Modulus Coeff. of Restitution

OFFSHORE LEADER

Offshore for 98 in / 2.5 meter piles and under

MINIMUM BOX LEAD SIZE / OPERATING LENGTH

Minimum Box Leader Size Operating Length for Offshore Leader 135 in (343 cm) 317,475 ft-lbs (430.42 kNm) 263,504 ft-lbs (357.25 kNm) 209,534 ft-lbs (284.07 kNm) 155,563 ft-lbs (210.90 kNm)

150 in (381 cm) 352,750 ft-lbs (478.24 kNm) 34-53

28,220 lbs (12,800 kg) 7,665 lbs (3,477 kg) 630.47 in² (4,067.54 cm²) 68,000 lbs (30,844 kg) Consult Factory

53 Gal (200.6 Liters) 8 Gal (30.28 Liters)

10 Gal/hr (37.8 Liters/hr) 1 Gal/hr (3.7 Liters/hr) 8 to 10 Pumps Every 20 Minutes of Operation Time.

> 1,036 lbs (470 kg) 25 in (63.5 cm) 491 in² (3,167.74 cm²) 8 in (20.32 cm)

Micarata / 2 each 25 in (63.5 cm) 1 in (2.54 cm)

Aluminum / 3 each 1/2 in (1.27 cm) 25 in (63.5 cm) 3.5 in (8.89 cm) 491 in² (3,167.74 cm²) 285 ksi (1,965 mpa) 0.8


Consult Factory

8 in x 43 in (20.32 cm x 109 cm) 408 in (1,036.32 cm)



Optional Variable Throttle Control





Aluminum MC 904

6" Well Stack up

NTION





WWW.AMERICANPILEDRIVING.COM Ape@americanpiledriving.com



Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice. Consult the factory for details on any specific product (800) 248-8498. Copyright © 2022 American Piledriving Equipment Inc. All Rights Reserved