

APE Single Acting Diesel Impact Hammer

THE WORLD'S LARGEST PILEDRIVERS

Model D220-42

SPECIFICATIONS

Stroke at Maximum Rated Energy 135 in (343 cm)

Maximum Rated Energy (Setting 4) 545,648 ft-lbs (739.76 kNm) 452,887 ft-lbs (614.00 kNm) (Setting 3)

360,127 ft-lbs (488.24 kNm) (Setting 2) (Setting 1) 267,367 ft-lbs (362.48 kNm)

Minimum Rated Energy (VARIABLE THROTTLE ALLOWS FOR INFINITE FUEL SETTING)

Maximum Obtainable Stroke 150 in (381 cm)

Maximum Obtainable Energy 606,275 ft-lbs (821.96 kNm) Speed (Blows Per Minute)

WEIGHTS (APPROXIMATE)

48,502 lbs (22,000 kg) Hammer Weight (Includes Trip Device) 112,300 lbs (50,938 kg)

Typical Operating (Weight With Offshore Leader) Consult Factory

CAPACITIES

Fuel Tank (Runs on Diesel or Bio-Diesel) 95 Gal (359.5 Liters) 26 Gal (98.4 Liters)

CONSUMPTION

Diesel or Bio-Diesel 18 Gal/hr (68.13 Liters/hr) Oil Tank 2 Gal/hr (7.57 Liters/hr)

Grease 8 to 10 Pumps Every 20 Minutes of Operation Time.

STRIKER PLATE

Weight 2,400 lbs (1,089 kg) Diameter 30 in (76.2 cm) 706 in² (4,555 cm²) Area Thickness 12 in (30.48 cm)

CUSHION MATERIAL

Micarata / 3 each Diameter-DB32 30 in (76.2 cm) Thickness 1 in (2.54 cm)

Type/Qty Aluminum / 4 each Thickness 1/2 in (1.27 cm) 30 in (76.2 cm) Diameter Total Combined Thickness 5 in (12.7 cm) 706 in² (4,555 cm²) Elastic-Modulus 285 ksi (1,965 mpa)


Coeff. of Restitution

OFFSHORE LEADER

Offshore for 98 in / 2.5 meter piles and under Consult Factory

MINIMUM BOX LEAD SIZE / OPERATING LENGTH

Minimum Box Leader Size 10 in x 60 in (25.4 cm x 152 cm) Hammer Operating Length with Box Helmet 432 in (1,097.28 cm)



Optional Variable Throttle Control



Cushion Material



Micarta / Conbest











