

APE Single Acting Diesel Impact Hammer

THE WORLD'S LARGEST PILEDRIVERS

Model D160-42

SPECIFICATIONS

Stroke at Maximum Rated Energy 135 in (343 cm)

Maximum Rated Energy (Setting 4) 396,844 ft-lbs (538.02 kNm) 329,380 ft-lbs (446.56 kNm) (Setting 3)

261,917 ft-lbs (355.09 kNm) (Setting 2) (Setting 1) 194,453 ft-lbs (263.63 kNm)

Minimum Rated Energy (VARIABLE THROTTLE ALLOWS FOR INFINITE FUEL SETTING)

Maximum Obtainable Stroke 150 in (381 cm)

Maximum Obtainable Energy 440,938 ft-lbs (597.80 kNm) Speed (Blows Per Minute)

WEIGHTS (APPROXIMATE)

Piston 35,275 lbs (16,000 kg) Anvil 10,223 lbs (4,637 kg) Anvil Cross Sectional Area 837.85 in2 (5,405.47 cm2) Hammer Weight (Includes Trip Device) 85,000 lbs (38,555 kg) Typical Operating (Weight With Offshore Leader) Consult Factory

CAPACITIES

Fuel Tank (Runs on Diesel or Bio-Diesel) 63 Gal (238.4 Liters) 11 Gal (41.63 Liters)

CONSUMPTION

Diesel or Bio-Diesel 12 Gal/hr (45.4 Liters/hr) Oil Tank 1 Gal/hr (3.7 Liters/hr)

Grease 8 to 10 Pumps Every 20 Minutes of Operation Time.

STRIKER PLATE

Weight 2,400 lbs (1,089 kg) Diameter 30 in (76.2 cm) 706 in² (4,555 cm²) Area Thickness 12 in (30.48 cm)

CUSHION MATERIAL

Micarata / 3 each Diameter-DB32 30 in (76.2 cm) Thickness 1 in (2.54 cm)

Type/Qty Aluminum / 4 each Thickness 1/2 in (1.27 cm) Diameter 30 in (76.2 cm) Total Combined Thickness 5 in (12.7 cm) 706 in² (4,555 cm²) Elastic-Modulus 285 ksi (1,965 mpa)

Coeff. of Restitution

OFFSHORE LEADER

Offshore for 98 in / 2.5 meter piles and under Consult Factory

MINIMUM BOX LEAD SIZE / OPERATING LENGTH

Minimum Box Leader Size 54 in (137 cm) Hammer Operating Length with Box Helmet 441 in (1,120.14 cm)




actual Model

Optional Variable Throttle Control



Cushion Material



Micarta / Conbest



MC 904 9" Well Stack up







