

# APE Model D36-26 Single Acting Diesel Impact Hammer

*D36-26 Finishing Dolphin Piles.*



## MODEL D36-26 (3.6 metric ton ram)

### SPECIFICATIONS

Stroke at maximum rated energy	135 in (343 cm)
Maximum rated energy (Setting 4)	89,302 ft-lbs (121,076 Nm)
Setting 3	74,450 ft-lbs (100,939 Nm)
Setting 2	59,201 ft-lbs (80,265 Nm)
Minimum rated energy (Setting 1)	43,952 ft-lbs (66,911 Nm)
<i>(Variable throttle allows for lower minimum energy and infinite fuel settings.)</i>	
Maximum obtainable stroke	157 in (381 cm)
Maximum obtainable energy	103,855 ft-lbs (140,807 Nm)
Speed (blows per minute)	34-53

### WEIGHTS

Ram	7,938 lbs (3,600 kg)
Anvil	1,358 lbs (616 kg)
Anvil cross sectional area	367.94 sq in (934.56 sq-cm)
Hammer weight (includes trip device)	14,894 lbs (6,754 kg)
Typical operating (weight with DB26 and H-beam insert)	17,546 lbs (7,811 kg)


### CAPACITIES

Fuel tank (runs on diesel or bio-diesel)	17.7 gal (67 liters)
Oil tank	5 gal (19 liters)


### CONSUMPTION

Diesel or Bio-diesel fuel	2.64 gal/hr (10 liters/hr)
Lubrication	.26 gal/hr (1 liters/hr)
Grease	8 to 10 pumps every 45 minutes of operation time.

*Optional Variable Throttle Control.*



*Drive Base Assembly.*



### STRIKER PLATE FOR DB 26

Weight	628 lbs (284 kg)
Diameter	22.5 in (57.15 cm)
Area	471 sq-in (696 sq-cm)
Thickness	6 inches (15.24 cm)

### CUSHION MATERIAL

Type/Qty	Micarta/2 ea
Diameter-DB26	22.5 in (57.15 cm)
Thickness	1 in (25.4 mm)
Type/Qty	Aluminum/3 ea
Thickness	1/2 in (12.7 mm)
Diameter	25 in (57.15 cm)
Total Combined Thickness	3.5 inches (8.89 cm)
Area	471 sq-in (696 sq-cm)
Elastic-modulus	285 ksi (1,965 mpa)
Coeff. of restitution	.8

### DRIVE CAP

DB 26:	1,076 lbs (488 kg)
--------	--------------------

### INSERT WEIGHT

H-Beam insert for 12" (305 mm) and 14" (355 mm):	948 lbs (430 kg)
Large pipe insert for sizes 12" to 24" diameter:	1,830 lbs (830 kg)

### MINIMUM BOX LEAD SIZE/OPERATING LENGTH

Minimum box leader size	8 in x 26 in (3.14 cm x 66 cm)
Operating length as described above	354 in (9 m)



Corporate Offices  
7032 South 196th  
Kent, Washington 98032 USA  
(800) 248-8498 & (253) 872-0141  
(253) 872-8710 Fax

Visit our WEB site:  
[www.apeibro.com](http://www.apeibro.com)  
e-mail: [ape@apeibro.com](mailto:ape@apeibro.com)